

APPLICATION FOR UNITED STATES PATENT IN THE NAME OF

**DAVID MONTGOMERY VARNON**

**JON JODY FONG**

**and**

**RAYMOND J. BISHOP**

ASSIGNED TO

**3D Systems, Inc.**

FOR

**QUANTIZED FEED SYSTEM FOR SOLID FREEFORM FABRICATION**

Docket No. **USA.229**

3D Systems, Inc.  
26081 Avenue Hall  
Valencia, CA 91355

Express Mail No. EF106052065US

## TITLE OF INVENTION

### QUANTIZED FEED SYSTEM FOR SOLID FREEFORM FABRICATION

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention.

The invention relates in general to a material feed system for solid freeform fabrication and, in particular, to a quantized feed system that can selectively feed discrete portions of material directly to a solid freeform fabrication device to build three-dimensional objects. Because the feed system is quantized, the system can be used to build three-dimensional objects in color or to dispense more than one material. In addition, the feed system can be integrated with a hermetically sealed waste removal system wherein reactive materials can be handled without special handling procedures.

### 2. Description of the Prior Art.

Recently, several new technologies have been developed for the rapid creation of models, prototypes, and parts for limited run manufacturing. These new technologies can generally be described as solid freeform fabrication, herein referred to as "SFF". Some SFF techniques include stereolithography, selective deposition modeling, laminated object manufacturing, selective phase area deposition, multi-phase jet solidification, ballistic particle manufacturing, fused deposition modeling, particle deposition, laser sintering, and the like. In SFF, complex parts are produced from a modeling material in an additive fashion as opposed to conventional fabrication techniques, which are generally subtractive in nature. For example, in conventional fabrication techniques material is removed by machining operations or shaped in a die or mold to near net shape and then trimmed. In contrast, additive fabrication techniques

incrementally add portions of a build material to targeted locations, typically layer by layer, in order to build a complex part.

SFF technologies typically utilize a computer graphic representation of a part and a supply of a build material to fabricate the part in successive layers. SFF technologies have many advantages over the prior conventional manufacturing methods. For instance, SFF technologies dramatically shorten the time to develop prototype parts and can quickly produce limited numbers of parts in rapid manufacturing processes. They also eliminate the need for complex tooling and machining associated with the prior conventional manufacturing methods, particularly when creating molds for casting operations. In addition, SFF technologies are advantageous because customized objects can be produced quickly by processing computer graphic data.

There are a wide variety of build materials that are used in various SFF techniques. These materials are typically applied in the form of a powder, liquid, gas, paste, foam, or gel. Recently, there has developed an interest in utilizing highly viscous paste materials in SFF processes to achieve greater mechanical properties. In addition, an interest has recently developed in reproducing visual features such as color on the three-dimensional objects produced by SFF processes. This has produced a need to develop special additives for the build materials along with new dispensing systems to enable the production of these visual features when building the three-dimensional objects.

One category of SFF that has emerged is selective deposition modeling, herein referred to as "SDM". In SDM, a build material is physically deposited in a layerwise fashion while in a flowable state and allowed to solidify to form an object. In one type of SDM technology the modeling material is extruded as a continuous filament through a resistively heated nozzle. In yet another type of SDM technology the modeling material is jetted or dropped in discrete droplets in order to build up a part. In one particular SDM apparatus, a thermoplastic material having a low-melting point is used as the solid

modeling material, which is delivered through a jetting system such as those used in ink jet printers. One type of SDM process utilizing ink jet print heads is described, for example, in U.S. Patent No. 5,555,176 to Menhennett, et al.

Because ink jet print heads are designed for use in two-dimensional printing, special modifications must be made in order to use them in building three-dimensional objects by SFF techniques. This is generally because there are substantial differences between the two processes requiring different solutions to different problems. For example, in two-dimensional printing a relatively small amount of a liquid solution is jetted and allowed to dry or solidify with a significant interest being given to print resolution. Because only a small amount of material is jetted in two-dimensional printing, the material reservoir for the liquid solution can reside directly in the ink jet print head while providing the ability to print numerous pages before needing to be refilled or replaced. In contrast, in SDM a normally solid material, such as a thermoplastic or wax material, must be heated to a flowable state in order to be jetted, and then allowed to solidify. Furthermore, in SDM dispensing resolution is not as critical as it is in two-dimensional printing. This is generally because, for each targeted pixel location, the amount of material to be jetted in SDM techniques is substantially greater than the amount to be jetted in two-dimensional printing techniques. For example, it may be required to deposit six droplets on a particular pixel location in SDM compared to just one or two droplets in two-dimensional printing. Although the targeting accuracy may be the same, the actual resolution achieved in SDM techniques is generally somewhat less than in two-dimensional printing because the six droplets dispensed may droop or slide towards adjacent pixel locations.

Another difference is that because of the substantially greater amount of material jetted in SDM, the rate at which objects are formed becomes important. Since achieving higher build rates in SDM has been a high priority, initial SDM techniques dedicated all the discharge orifices in the ink jet print heads to dispense a single build

material to maximize the build rate of forming the three-dimensional object. However, this sacrifices the ability to selectively dispense multiple colors from the print head when forming the object.

The differences mentioned above are significant and create a number of problems to be resolved. For instance, the amount of material deposited in SDM techniques, both in volume and in mass, can be so substantial that it is generally considered impractical to mount a reservoir directly on the ink jet print head to hold all of the material. Thus, it is typical in most SDM systems to provide a large reservoir at a remote location from the print head that is in communication with the ink print head via a material delivery system having a flexible umbilical cord. However, the large container and umbilical cord must be heated to cause at least some of the build material to become or remain flowable so that the material can flow to the dispensing device. Undesirably, start up times are longer for SDM techniques using ink jet print heads than in two-dimensional printing with ink jet print heads due to the length of time necessary to initially heat the solidified material in the large remote reservoir to its flowable state. In addition, a significant amount of energy is required to maintain the large quantity of material in the flowable state in the reservoir and in the delivery system during the build process. This undesirably generates a significant amount of heat in the build environment.

As higher build speeds have been a priority in SDM techniques, previous expedients have abandoned the color dispensing capabilities of the ink jet print heads and have instead dedicated all of the dispensing orifices of the print heads to dispensing a single build material provided from a single large reservoir. According to these prior art delivery systems multiple remote reservoirs and delivery systems would be necessary in order to dispense multiple materials to produce multiple colors in an object. This would multiply the complexity and cost of such a system and is generally not practical. Thus, there is a need to overcome the limitations of the prior art SFF feed

systems that utilize a remotely heated material reservoir. There is also a need to develop a feed system for an ink jet print head used in SFF that can take advantage of the color dispensing capabilities of the print heads.

Previous expedients have been proposed for delivering a phase change ink to a print head for two dimensional printing. For example, in U.S. Patent No. 5,861,903 to Crawford et al., a supply of ink sticks or blocks are linearly stacked in a loading bin that biases the stick at the end of the stack against a melt plate and the melted ink then drips into the print head in a liquid state. Similarly in U.S. Patent No. 4,593,292 to Lewis and in U.S. Patent No. 4,609,924 to De Young, a long block of solid ink is biased against a heater plate to melt the ink for delivery of the melted ink to a print head. Also, in U.S. Patent No. 4,636,803 a supply of cylindrical pellets of solid ink are advanced along an elongated array prior to being melted for use by an ink jet print head. In U.S. Patent No. 4,631,557 to Cook et al., a cartridge holding a phase change material is heated to allow the melted material to drain into a supply system for a print head. In U.S. Patent No. 4,682,185 to Martner, a flexible web of hot melt ink is advanced on a spool to a heater where the material is then melted prior to delivery to a ink jet print head. In U.S. Patent No. 5,341,164 to Miyazawa et al., a number of embodiments of an ink jet supply system are disclosed. In one embodiment an elongated array of solid ink is advanced and broken off at cutouts prior to being melted. In another embodiment, a vertical array of solid spheres of ink are held in single file and are selectively dropped into the print head. However, these prior expedients are directed to feed systems for two-dimensional printing and do not address the problems confronted in SDM techniques, such as how to handle and deliver the significantly larger quantity of build material needed to form three-dimensional objects. For example, the prior linear or array feed systems, if used for SDM, would have to be extremely long in order to hold the quantity of material needed, or require constant manual refilling during the build process. Neither of these alternatives are desirable in SDM.

Another problem that is unique to SDM techniques is that the layers being formed must be shaped or smoothed during the build process to establish a uniform layer. Normalizing the layers is commonly accomplished with a planarizer that removes a portion of the material dispensed in the layers. One such planarizer is disclosed in U.S. Patent No. 6,270,335 to Leyden et al. However, the planarizer produces waste material during the build process that must be handled. Normally this is not a concern when working with non-reactive materials; however, it can become a problem when reactive materials are used. For example, most photopolymers are reactive, and excessive contact to human skin may result in sensitivity reactions. Thus, most all SFF processes that utilize photopolymer materials require some additional handling procedures in order to minimize or eliminate excessive physical contact with the materials. For example, in stereolithography, operators typically wear gloves when handling the liquid resin and when removing finished parts from the build platform. However, SDM operators who normally handle non-reactive materials consider additional handling procedures inconvenient and, if possible, would prefer they be eliminated. Thus, there is a need to provide a material feed and waste system for SDM that can handle reactive materials without requiring the implementation of special handling procedures.

These and other difficulties of the prior art are overcome according to the present invention by providing build material to the dispensing device of a SFF apparatus in discrete portions on an as needed basis when the apparatus is forming a three-dimensional object.

## BRIEF SUMMARY OF THE INVENTION

The present invention provides its benefits across a broad spectrum of SFF processes by providing a build material to the dispensing device of a SFF apparatus in discrete portions on an as needed basis when forming a three-dimensional object.

It is one aspect of the present invention to provide a new build material feed system for an SFF apparatus which overcomes the above-mentioned disadvantages of the prior art.

It is another aspect of the present invention to provide a new build material feed system for an SFF apparatus that takes advantage of the multiple color dispensing capabilities of an ink jet print head when forming three-dimensional objects.

It is a feature of the present invention that the feed system delivers the build material to the dispensing device as needed in discrete amounts to form three-dimensional objects.

It is still another feature of the present invention that the build material delivered by the feed system is heated to a flowable state adjacent the dispensing device and is passed through a capillary valve into to a dispensing chamber which is maintained at sub-atmospheric pressure.

It is an advantage of the present invention that it is no longer necessary to maintain a large quantity of build material in a flowable state in a remote reservoir at an elevated temperature in an SDM apparatus.

It is another advantage of the present invention that materials can be used by an SDM apparatus without requiring the implementation of special handling procedures for the material.

It is yet another advantage of the present invention that the amount of radiant heat generated by an SDM apparatus is substantially reduced.

It is still yet another advantage of the present invention feed system that ink jet print heads can be utilized to build three-dimensional objects by SFF techniques having



visual attributes such as color.

These and other aspects, features, and advantages are achieved according to the method and apparatus of the present invention that employs a unique build material feed system that delivers a discrete amount of build material on an as needed basis in a non-flowable state to a dispensing device. After the material is delivered to the dispensing device, it is changed from the non-flowable state to a flowable state wherein it may then be selectively dispensed to form a three-dimensional object in a layerwise fashion.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000

## BRIEF DESCRIPTION OF THE DRAWINGS

These and other aspects, features and advantages of the present invention method and apparatus will become apparent upon consideration of the following detailed disclosure of the invention, especially when it is taken in conjunction with the accompanying drawings wherein:

FIG. 1 is a diagrammatic side view of a prior art solid deposition modeling apparatus.

FIG. 2 is a diagrammatic side view of an embodiment of the present invention feed system for use with the solid deposition modeling apparatus of FIG. 1.

FIG. 3 is a diagrammatic side view of a portion of the present invention feed system shown attached to an ink jet print head.

FIG. 4 is a diagrammatic isometric view of an alternate embodiment of the present invention feed system.

FIG. 5 is a diagrammatic isometric view of a container for holding a discrete amount of build material for use in the embodiment shown in FIG. 4.

FIG. 6 is a cross-sectional view of the waste receptacle associated with the container shown in FIG. 5.

FIG. 7 is a schematic view of a preferred embodiment of the present invention.

FIG. 8 is a isometric view of a SDM apparatus of the embodiment shown schematically in FIG. 7

To facilitate understanding, identical reference numerals have been used, where possible, to designate identical elements that are common to the figures.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention provides its benefits across a broad spectrum of SFF processes. While the description which follows hereinafter is meant to be representative of a number of such applications, it is not exhaustive. As will be understood, the basic apparatus and methods taught herein can be readily adapted to many uses. It is intended that this specification and the claims appended hereto be accorded a breadth in keeping with the scope and spirit of the invention being disclosed despite what might appear to be limiting language imposed by the requirements of referring to the specific examples disclosed.

While the present invention is applicable to all SFF techniques and objects made therefrom, the invention will be described with respect to solid deposition modeling utilizing a build material that is dispensed in a flowable state. However it is to be appreciated that the present invention can be implemented with any SFF technique utilizing a wide variety of build materials. For example, the build material can be a photocurable or sinterable material that is heated to a flowable state but when solidified may form a high viscosity liquid, a semi-solid, a gel, a paste, or a solid. In addition, the build material may be a composite mixture of components, such as a mixture of photocurable liquid resin and powder material such as metallic, ceramic, or mineral, if desired.

As used herein, the term "a flowable state" of a build material is a state wherein the material is unable to resist shear stresses that are induced by a dispensing device, such as those induced by an ink jet print head when dispensing the material, causing the material to move or flow. Preferably the flowable state of the build material is a liquid state, however the flowable state of the build material may also exhibit thixotropic properties. The term "solidified" and "solidifiable" as used herein refer to the phase change characteristics of a material where the material transitions from the flowable state to a non-flowable state. A "non-flowable state" of a build material, as used herein,

is a state wherein the material is sufficiently self-supportive under its own weight so as to hold its own shape. A build material existing in a solid state, a gel state, a paste state, or a thixotropic state, are examples of a non-flowable state of a build material for the purposes of discussion herein. Further, the term "cured" or "curable" refers to any polymerization reaction. Preferably the polymerization reaction is triggered by exposure to radiation or thermal heat. Most preferably the polymerization reaction involves the cross-linking of monomers and oligomers initiated by exposure to actinic radiation in the ultraviolet or infrared wavelength band. Further, the term "cured state" refers to a material, or portion of a material, in which the polymerization reaction has substantially completed. It is to be appreciated that as a general matter the material can easily transition between the flowable and non-flowable state prior to being cured, however, once cured, the material cannot transition back to a flowable state and be dispensed by the apparatus. Additionally, the term "support material" refers to any material that is intended to be dispensed to form a support structure for the three-dimensional objects as they are being formed, and the term "build material" refers to any material that is intended to be dispensed to form the three-dimensional objects. The build material and the support material may be similar materials having similar formulations but, for purposes herein, they are to be distinguished only by their intended use. A preferred method for dispensing a curable phase change material to form a three-dimensional object and for dispensing a non-curable phase change material to form supports for the object is disclosed in the concurrently filed U.S. Patent Application under docket number USA.282 entitled "Selective Deposition Modeling with Curable Phase Change Materials", which is herein incorporated by reference as set forth in full. A preferred curable phase change material and non-curable phase change support material is disclosed in the concurrently filed U.S. Patent Application under docket number USA.269 entitled "Ultra-Violet Light Curable Hot Melt Composition", which is herein incorporated by reference as set forth in full.

Referring particularly to Fig. 1, there is illustrated generally by the numeral 11 a prior art SDM apparatus that can be adapted to incorporate the present invention build material feed system. The SDM apparatus 11 is shown building a three-dimensional object 20 in a build environment indicated generally by the numeral 13. The object is built in a layer by layer manner on a build platform 15 that can be precisely positioned vertically by any conventional actuation means 17. The object is built in a layerwise manner by dispensing a build material in a flowable state. Generally, the build material is normally in a non-flowable state and changes to a flowable state when maintained at or above the flowable temperature of the material. The build environment 13 is maintained at a temperature below the flowable temperature of the build material so that the three-dimensional part will solidify as the build material is dispensed. Directly above and parallel to the build platform 15 is a rail system 19 on which a trolley 21 carrying a dispensing device 14 resides.

Generally, the trolley carrying the dispensing device is fed a build material 23 from a remote reservoir 25 due to the large quantity of material typically needed to be dispensed by the SDM apparatus to build a three-dimensional object. In order to dispense the material, a heating means must be provided to heat the material to a flowable state in the reservoir 25 and to maintain the temperature of the material above the flowable temperature of the build material. Preferably, the flowable state of the build material is a liquid state. Changing the material to the flowable state is initially achieved and maintained by the provision of heaters 49 on the reservoir 25 and by the provision of heaters (not shown) on the umbilical 51 connecting the reservoir 25 to the dispensing device 21. Located on the dispensing device 21 is at least one discharge orifice 27 for dispensing the build material. A reciprocating means is provided for the dispensing device 21 which is reciprocally driven on the rail system 19 along a horizontal path by a conventional drive means 29 such as an electric motor. Generally, the trolley carrying the dispensing device 21 takes multiple passes to dispense one complete layer of

material from the discharge orifice 27. In Fig. 1, a portion of a layer of dispensed material 31 is shown as the trolley has just started its pass from left to right. A dispensed droplet 33 is shown in mid-flight, and the distance between the discharge orifice 27 and the layer 31 of build material is greatly exaggerated for ease of illustration. Also shown in Fig. 1, is a planarizer 39 that is used to successively shape the layers as needed. Such shaping is typically needed in order to eliminate the accumulated effects of drop volume variation, thermal distortion, and the like, which occur during the build process. After shaping, a smooth uniform layer is achieved as indicated by numeral 41. Excess material 43 removed by the planarizer 39 travels through a waste umbilical 47 to waste bin 45. The waste material 43 may be discarded or recycled, which generally depends on the nature of the material and the operating characteristics of the system.

Preferably, a remote computer 35 takes a CAD data file and generates three-dimensional coordinate data of an object, commonly referred to as an STL file. When a user desires to build an object, a print command is executed at the remote computer in which the STL file is processed through print client software that is sent to the SDM apparatus 11 as a print job. The print job is processed and transmitted to the SDM apparatus by any conventional data transferable medium desired, such as by magnetic disk tape, microelectronic memory, or the like. The data transmission route and controls of the SDM apparatus are represented as dashed lines at 37. The data is processed into a prescribed pattern for each layer of the three-dimensional object to be built. A computer controller (not shown) utilizes the prescribed pattern data to produce the appropriate control commands to operate the apparatus to form the three-dimensional object.

Now, according to the present invention, a new build material feed system generally shown by the numeral 10 in FIG. 2 and may be used in conjunction with the prior art solid deposition modeling apparatus 11 shown in FIG. 1. Advantageously, the

new build material feed system 10 eliminates the reservoir 25, the umbilical 51, and the heater elements 49 attached to the reservoir of the prior art apparatus. The new method for dispensing the build material by the present invention apparatus comprises providing at least one queue station for holding a plurality of discrete amounts of a build material in a non-flowable state. A plurality of discrete amounts of build material are then loaded in the queue station in a random order. A discrete amount of build material is then delivered to at least one hopper on the dispensing device. The discrete amount of build material is then changed from the non-flowable state to the flowable state. The build material in the flowable state is then moved to a receptacle of the dispensing device and is finally dispensed in the flowable state in a layerwise fashion to form layers of a three-dimensional object. An additional step of providing an environment for the build material to return to the non-flowable state after being dispensed in a layer may be implemented, if needed.

In one embodiment, the discrete non-flowable build material is delivered in a drop-in-load manner to hoppers located on the dispensing devices. The hoppers are provided with heaters which induce the build material to change to the flowable state. The hoppers are in communication with a receptacle via a passageway wherein the flowable build material is delivered through the passageway and into the volume of the receptacle which holds the material in the flowable state. The material is then dispensed through the discharge orifices of the dispensing device. In one embodiment the passageway comprises a capillary valve having an effective capillary force greater than the capillary force of the discharge orifices to allow the flowable build material to be drawn into the receptacle. The receptacle is maintained at sub-atmospheric pressure so as to prevent the build material from draining from the discharge orifices, and also to assist in drawing new build material into the receptacle from the hopper. In another embodiment, at least one hopper and at least one receptacle is provided for each dispensing device.

Preferably the dispensing device is an ink jet print head although other dispensing devices may be used, if desired. In one embodiment, at least one hopper is provided with a dispensing device for receiving a build material to be dispensed to form the three-dimensional object, and at least one hopper is provided with the dispensing device for receiving a support material for forming a support structure for the object. In another embodiment, one ink jet print head dispenses a build material to form the three-dimensional object and another ink jet print head dispenses a support material to form supports for the object.

In yet another embodiment, each hopper is associated with a unique visual characteristic and discrete amounts of build material indicative of the associated visual characteristic are delivered to the appropriate hoppers. Preferably, a color additive such as a dye or pigment is provided in the discrete amounts of build material for the colors cyan, magenta, yellow, and black. The different colored build materials are selectively delivered to the specific hoppers to enable the SFF apparatus to form three-dimensional objects in color. This is accomplished by providing a plurality of discharge orifices to be in communication with each receptacle associated with a given hopper so that the dispensing device can selectively dispense the build material with any color additive to any coordinate in any layer on the three-dimensional object.

Alternatively, the hoppers may be associated with different mechanical properties related to different formulations of build materials in which the discrete build material feed system would enable the formation of non-homogeneous three-dimensional objects by any SFF technique.

In a preferred embodiment, the feed system is integrated with a waste removal system and the discrete amounts of build material are provided in containers. The containers include a waste receptacle wherein waste material generated when shaping the layers is deposited into the waste receptacle. Preferably the feed system handles two separate materials, one being a build material to form the object and the other being



a support material for supporting the object during the build process. Once substantially all of the material in a container has been dispensed, the waste receptacle containing the waste material is hermetically sealed shut and the container is ejected.

Advantageously, the containers can be handled without requiring any special handling procedures for the waste material. This makes the waste safe for disposal such as by delivery to a facility that can remove the waste material and recycle the containers, if desired. Alternatively, if the waste material is reactive to actinic radiation it may be cured by exposure to such radiation in the waste receptacle, if desired.

Now referring back to FIG. 2, the build material feed system 10 generally comprises a dispensing device 14 and a build material delivery means generally shown by numeral 34. In this embodiment the build material delivery means can more generally be described as a mechanical indexer capable of delivering discrete amounts of non-flowable build material on an as needed basis to the dispensing device 14. Discrete amounts of build material are shown by numeral 18, which in this embodiment are spherically shaped having an average spherical diameter of approximately one inch. However, the shape of the discrete amounts of build material may be cubic, conical, cylindrical, or the like. They may also be formed in any common uniform shape such as, for example, the shapes commonly used in the pharmaceutical industry for tablets and pills. They may also take the shape of pellets or may even be granules. Alternatively the shapes may be non-uniform or random, if desired.

Before the discrete amounts of build material are delivered to the dispensing device, they are held in material queue stations generally shown by the numeral 12. The queue stations are established by the provision of at least one holding bin shown by the numeral 36. Preferably each holding bin only contains a plurality of discrete amounts of build material that all have a common characteristic, for example, such as containing the same color additive, the same material formulation, or the like. Importantly, a large quantity of discrete amounts of build material are contained in the

queue stations since most SDM techniques must dispense a must larger quantity of material from the printhead compared to the quantity of material dispensed in two-dimensional printing techniques. As such, the queue stations 36 are substantially large, and as shown in Fig. 2, the discrete amounts of build material 18 are randomly placed within the queue station. In this configuration, the random placement of the material 18 in the queue stations saves a significant amount of space in the apparatus compared to stacking the material in a linear fashion.

Shown by numerals 38A through 38D are dispensing actuators which deliver the discrete amounts of build material to the hoppers 16 located on the dispensing device 14. Preferably there is one hopper 16 for each material queue station 12, and at least one hopper 16 for each dispensing device 14. When a hopper is low on build material, the computer control system (not shown) activates the appropriate dispensing actuator (38A through 38D) to deliver a discrete amount of build material 18 to the hopper 16. Preferably, a sensor (not shown) is provided for each hopper 16 which detects a low condition of the hopper. In response to the low condition, the computer control system delivers a signal to the dispensing actuator associated with the hopper in the low condition. This signal triggers the dispensing actuator to deposit a discrete amount of build material to the hopper. For example, shown by numeral 18A in FIG. 2, a discrete amount of build material is in mid-flight being delivered to the hopper 16. This demonstrates a drop-in-load manner of delivering the build material to the dispensing device 14.

The present invention is unique in that the discrete amounts of unused build material 18 are delivered on an as-needed basis to the dispensing device 14 in a non-flowable state. This discrete or quantized approach to delivering build material to the dispensing device of an SFF apparatus produces significant advantages over prior art SFF systems. One advantage is that it completely eliminates the prior art heated reservoir and umbilical delivery system. More importantly the system is readily

adaptable for dispensing any number of different build materials simultaneously. For example, color additives such as dyes or pigments can be premixed in the discrete amounts of build material 18 which are then delivered to their respective hoppers on the dispensing device 14 in order to build three-dimensional objects in color.

The next step in the build material feed system once the discrete amounts of build material 18 have been delivered to the hopper 16 is to change the non-flowable state of the build material to a flowable state. Preferably, a heating means is provided on the dispensing device, such as by the provision of heater elements (not shown) on the dispensing device and hopper in order to raise the temperature of the material to change from the non-flowable to a flowable state. The change in state is shown in FIG. 2 by numerals 18B, 18C and 18D, wherein the build material is shown progressively changing from the non-flowable state to the flowable state. Shown in FIG. 3, the hopper 16 includes a containment wall 26 which may also be used to transfer heat to the discrete amount of build material 18 causing it to transition to the flowable state, as shown by numeral 32. It is in this flowable state where the build material is capable of being delivered to the receptacle to be selectively dispensed by the discharge orifice 27 of the dispensing device. Although only one hopper 16 and receptacle 22 are shown in FIG. 3, any number or combination may be used for each dispensing device, as desired.

Now referring to FIG. 3, a diagrammatic cross-sectional view is shown of the dispensing device 14. The dispensing device 14 is provided with a receptacle 22 that is in communication with the hopper 16 via a passageway or capillary valve 24. The receptacle contains a volume of build material in a flowable state as identified by numeral 30. Preferably, the passageway is a capillary valve having an effective capillary force that is greater than the capillary force of the discharge orifice 27. Typically the capillary force of most ink jet print heads is between about 3 to 9 inches of H<sub>2</sub>O. Thus, it is desirable to select a porous material for the capillary valve 24 having

an effective capillary force greater than about 9 inches of H<sub>2</sub>O. Satisfactory results can be achieved using metal mesh filters having an effective capillary force of between about 25 to 60 inches of H<sub>2</sub>O. With sub-atmospheric pressure being applied to the receptacle 22, the flowable build material 32 is drawn through the capillary valve or passage 24 and into the receptacle 22. Shown in FIG. 3 the sub-atmospheric pressure is applied to the volume of material in the receptacle 22 via a vacuum line connection 28. Alternatively the receptacle may comprise a generally sealed membrane, or the like, and the sub-atmospheric pressure can be established by providing a biasing spring inside the membrane, if desired. Generally the sub-atmospheric pressure is needed to prevent the flowable build material in the reservoir 30 from draining through the discharge orifice 27 when the ink jet print head is not in use. The capillary valve shown in FIG. 3 is conceptually similar to that as disclosed in U.S. Pat. No. 5,280,300 to Fong et al. wherein the capillary valve is used in connection with refilling an aqueous ink solution into an ink jet cartridge.

Preferably, the upper surface level 40 of the flowable build material 30 in receptacle 22 is monitored by a sensor (not shown). As the material is being dispensed from the discharge orifice 27, the volume of flowable build material 30 in the receptacle starts to decrease, resulting in a low condition that is detected by the sensor. The sensor then provides a signal to the computer controller which in turn signals the appropriate dispensing actuator (38A-38D) to delivering another discrete amount of non-flowable build material 18 into the hopper 16. This unused material then changes to the flowable state, for example by the application of heat, and is drawn into the receptacle 22 to replenish the supply of flowable build material 30. Thus, the sensor(s), the dispensing actuator(s), and computer control system operably function to deliver the discrete amounts of build material to the hoppers on an as-needed basis.

It is to be appreciated that a unique feature of the present invention is that discrete non-flowable amounts of build material are selectively delivered directly to the

dispensing device. Many advantages are achieved by delivering discrete non-flowable amounts of build material to the dispensing device. For example, there is no longer a need to provide a large heated remote container of flowable material delivered via an umbilical cord to the dispensing device. This eliminates a substantial amount of heat previously provided to maintain the material in the flowable state. However, there are other unique advantages to the present invention. Because discrete amounts of material are selectively delivered to the various hoppers, the system can be easily adapted to either selectively dispense different materials, or to selectively dispense a single build material with different additives such as pigments or dyes, if desired.

For example, in one embodiment a hopper may be dedicated to deliver a build material that is dispensed exclusively for building the three-dimensional object 20 while other hoppers may be dedicated to delivering a build material to be dispensed exclusively for forming a support structure for the three-dimensional object.

Alternatively, there could be more than one dispensing device 14, i.e. ink jet print head, where one could be dedicated to exclusively dispense build material to form the three-dimensional object, and another could be dedicated to exclusively dispense the support material to form a support structure for the three-dimensional object, as needed.

In another embodiment the dispensing device 14 may have a plurality of hoppers 16 wherein each hopper is associated with a unique visual characteristic. The unique visual characteristic associated with the hoppers may be indicative of color, shading, texture, fluorescence, or translucency. For example, if color were the unique visual characteristic associated with the hoppers, tablets or pellets of the build material in which a color additive has already been included would be delivered exclusively to a hopper associated with that color. Thus, it is envisioned that the discrete amounts of build material may be selectively delivered to the hoppers with specific color additives to enable the ink jet print head to build three-dimensional objects in color. In one embodiment, color additives indicative of cyan, magenta, yellow, and black may be

provided to the discrete amounts of build material and selectively delivered to hoppers associated with cyan, magenta, yellow and black. The hoppers may then be in communication with receptacles allowing the build material of the different colors to be selectively dispensed to any coordinate of any layer of the three-dimensional object. Preferably, a plurality of discharge orifices are provided that are in communication with each receptacle associated with each hopper such that the dispensing device can selectively dispense the build material with any color additive to any coordinate of the three-dimensional object. Thus, it is envisioned that three-dimensional color building may be achieved in SDM by utilizing the unique dispensing device of the present invention.

Alternatively, the hoppers could be associated with different mechanical properties of different build material formulations. For example, build materials having different mechanical properties could be selectively dispensed to any coordinate in any layer of the three-dimensional object. This would desirably produce composite non-homogeneous three-dimensional objects, for example, such as part ceramic and part metallic objects.

The dispensing device shown in the FIG. 1 reciprocates in a horizontal plane while the build platform remains stationary. However other motion means may be used for moving the dispensing device and the build platform respectively when dispensing the build material. For example, the dispensing device could be held stationary and the build platform could be reciprocated, if desired, as shown in FIG. 7. Further, both the dispensing device and the build platform may reciprocate, if desired. In addition, if two or more dispensing devices are used, they may be configured to reciprocate in different directions within a horizontal plane, if desired. Alternatively the motion means does not need to rely on reciprocation. For example the build platform could continuously rotate about an axis adjacent a stationary dispensing device, and vice versa, if desired.

Referring to FIG. 4, a preferred embodiment of the build material feed system 10

is shown. In this embodiment the queue station 12 forms a magazine for holding a plurality of containers 42. The containers hold a discrete amount of build material that is initially in a non-flowable state. Preferably the containers 42 are cartridges containing unused material and are initially loaded into the magazine manually by an operator, however the loading process could be automated, if desired. In this embodiment the cartridges are stacked in a linear fashion. By providing a significantly large amount of build material in each cartridge, the length of the magazine can be minimized to an acceptable size, making linear stacking of the cartridges feasible. Providing a significantly large amount of build material in the cartridges is possible since the material in each cartridge is slowly expelled as needed to feed to the print head instead of being delivered all at once to the print head. The hopper comprises a mechanical indexer 44 that receives the cartridges and then rotates them into a position where an extrusion bar 46 applies force to the cartridge to remove the build material from the cartridge. The material is removed through an orifice at its end (shown at 70 in FIG. 5) and into a filter 48. The extrusion bar 46 is biased axially along a shaft 54 by a feed motor 52. As the extrusion bar 46 applies the force to expel the build material, the material passes through the filter 48 and is delivered to the dispensing device 14.

It is to be appreciated that the amount of force applied by the extrusion bar exerts a substantial amount of shear stress on the material in the cartridge to expel the material. The amount of this force is so substantial that the material need not be in a flowable state to be expelled from the cartridge. Depending on the build material and the specifications of the dispensing device, the filter may be omitted. However, if an ink jet print head is used as the dispensing device, it may be desirable to run the build material through a 5-micron filter prior to delivering the material to the print head. Alternatively the filter may be omitted from the SDM apparatus if the material is run through a filter prior to loading the material in the cartridges. In this embodiment the discrete amounts of build material in the cartridges are delivered to the queue station 12

while the build material is in a non-flowable state. Heater elements, identified by numeral 50 are situated on the queue station 12, on the indexer 44, on the filter 48, and on the dispensing device 14. The heater elements 50 provide thermal heat to change the build material to the flowable state and to maintain the build material in the flowable state as it moves through the delivery system to the print head. Preferably the build material transforms from the non-flowable state to the flowable state in the cartridge prior to being delivered to the indexer 44, although this is not required.

Unique to the embodiment in FIG. 4 is the integration of a waste removal means with the build material feed system 10. Waste material (shown in FIG. 7 by numerals 58, 92, and 43) generated during planarizing is returned through a waste umbilical 56 and is delivered to a waste receptacle 60 provided on the container 42. The waste removal means is unique in that it can take reactive waste material, such as an uncured photopolymer material, and hermetically seal the waste material in each cartridge prior to ejecting each cartridge. Desirably, the sealed and ejected containers 66 can be directly handled by personnel in an office environment thereby eliminating the need for special handling procedures for the waste material.

Referring particularly to FIG. 7 there is illustrated generally by the numeral 86 a preferred solid freeform fabrication apparatus. This apparatus 86 is shown including schematically the material feed and waste system 10 of FIG. 4. In contrast to the prior art apparatus shown in FIG. 1, the build platform 15 is reciprocally driven by the conventional drive means 29 instead of the dispensing trolley. The dispensing trolley 21 is precisely moved by actuation means 17 vertically to control the thickness of the layers of the object 20. Preferably the actuation means 17 comprises precision lead screw linear actuators driven by servomotors. In the preferred embodiment the ends of the linear actuators 17 reside on opposite ends of the build environment 13 and in a transverse direction to the direction of reciprocation of the build platform. However for ease of illustration in FIG. 7 they are shown in a two-dimensionally flat manner giving



the appearance that the linear actuators are aligned in the direction of reciprocation of the build platform 15. Although they may be aligned with the direction of reciprocation it is preferred they be situated in a transverse direction so as to optimize the use of space within the apparatus.

In the build environment generally illustrated by numeral 13, there is shown by numeral 20 a three-dimensional object being formed with integrally formed supports 53. The object 20 and supports 53 both reside in a sufficiently fixed manner on the build platform 15 so as to sustain the acceleration and deceleration effects during reciprocation of the build platform while still being removable from the platform. In order to achieve this, it is desirable to dispense at least one complete layer of support material on the build platform before dispensing the build material since the support material is designed to be removed at the end of the build process. In this embodiment, the material identified by numeral 23A is dispensed by the apparatus 10 to form the three-dimensional object 20, and the material identified by numeral 23B is dispensed to form the support 53. Containers identified generally by numerals 42A and 42B respectively hold a discrete amount of these two materials 23A and 23B. Umbilicals 51A and 51B respectively deliver the material to dispensing device 27, which in the preferred embodiment is an ink jet print head having a plurality of dispensing orifices.

Preferably the materials 23A and 23B are phase change materials that are heated to a liquid state, and heaters (not shown) are provided on the umbilicals 51A and 51B to maintain the materials in a flowable state as they are delivered to the dispensing device 27. In this embodiment the ink jet print head is configured to dispense both materials from a plurality of dispensing orifices so that both materials can be selectively dispensed in a layerwise fashion to any location in any layer being formed. When the dispensing device 27 needs additional material 23A or 23B, extrusion bars 46A and 46B are respectively engaged to extrude the material from the containers 42A and 42B, through the umbilicals 51A and 52B, and to discharge orifices 27 of the dispensing

device 14.

The dispensing trolley 21 in the embodiment shown in FIG. 7 comprises a heated planarizer 39 that removes excess material from the layers to normalize the layers being dispensed. The heated planarizer contacts the material in a non-flowable state and because it is heated, locally transforms some of the material to a flowable state. Due to the forces of surface tension, this excess flowable material adheres to the surface of the planarizer, and as the planarizer rotates the material is brought up to the skive 90 which is in contact with the planarizer 39. The skive 90 separates the material from the surface of the planarizer 39 and directs the flowable material into a waste reservoir identified generally by numeral 94 located on the trolley 21. A heater 96 and thermistor 98 on the waste reservoir 94 operate to maintain the temperature of the waste reservoir at a sufficient level so that the waste material in the reservoir remains in the flowable state.

The waste reservoir is connected to a heated waste umbilical 56 for delivery of the waste material to the waste receptacles 60A and 60B. The waste material is allowed to flow via gravity down to the waste receptacles 60A and 60B. Although only one umbilical 56 with a splice connection to each waste receptacle is shown, it is preferred to provide a separate waste umbilical 56 between the waste reservoir 94 and each waste receptacle 60A and 60B.

For each waste receptacle 60A and 60B, there is associated a solenoid valve 100A and 100B, for regulating the delivery of waste material to the waste receptacles. Preferably the valves 100A and 100B remain closed, and only open when the respective extrusion bars 46A and 46B are energized to remove additional material. For example, if only extrusion bar 46A is energized, only valve 100A is opened to allow waste material 43 to be dispensed into the waste receptacle 60A. This feedback control of the valves prevent delivery of too much waste material to either waste receptacle, by equalizing the delivery of waste material in the waste receptacles in proportion to the

rate at which material is fed from the containers to the dispensing device. Thus, the delivery of waste material to the waste receptacles is balanced with the feed rates of build material and support material of the feed system.

In the embodiment of FIG. 7, an additional detection system is provided in the waste system to prevent the waste material from overflowing the waste reservoir 94. The system comprises an optic sensor 102 provided in the waste reservoir 94 that detects an excess level of waste material in the reservoir. If the level of the waste material in the waste reservoir 94 raises above a set level, it is detected by the sensor 102. The sensor 102 in turn provides a signal to the computer controller which shuts down the apparatus. This prevents waste material from flooding the components inside the apparatus in the event of a malfunction of the feed and waste system. The apparatus can then be serviced to correct the malfunction thus preventing excessive damage to the apparatus.

In the preferred embodiment shown in FIG. 7, the build material 23A is a phase change material that is cured by exposure to actinic radiation. After the curable phase change material 23A is dispensed in a layer it transitions from the flowable state to a non-flowable state. After a layer has been normalized by the passage of the planarizer 39 over the layer, the layer is then exposed to actinic radiation by radiation source 88. Preferably the actinic radiation is in the ultraviolet or infrared band of the spectrum. It is important, however, that planarizing occurs prior to exposing a layer to the radiation source 88. This is because the preferred planarizer can only normalize the layers if the material in the layers can be changed from the non-flowable to the flowable state, which cannot occur if the material 23A is first cured.

In conjunction with the curable build material 23A, a non-curable phase change material is used for the support material 23B. Since the support material cannot be cured, it can be removed from the object and build platform, for example, by being dissolved in a solvent. Alternatively the support material can be removed by

application of heat to return the material to a flowable state, if desired.

In this embodiment the waste material comprises both materials as they accumulate during planarizing. Preferably, a second radiation source 70 is provided to expose the waste material in the waste receptacles to radiation to cause the material 23A to cure so that there is no reactive material in the waste receptacles.

A preferred embodiment of the containers 42 for use in the feed and waste system are shown in FIGS. 5 and 6. Each container 42 comprises a syringe portion 62 and plunger portion 64. The syringe portion forms a cylinder having a small opening 70 at one end for dispensing the material. A flange 72 is provided on the end opposite the small opening, which acts as a key for loading the containers into the hopper. The plunger portion 64 comprises a piston end 74 which bears against the material in the cylinder of the syringe portion 62. The plunger portion 64 also has a sealing end 76 which, as shown in FIG. 4, when the container is loaded into and held in place by the indexer 44, is acted on by the extrusion bar 46 which drives the plunger portion into the syringe portion. As the plunger portion 64 is driven into the syringe portion 62 the material in the syringe portion is expelled through the small opening 70.

Preferably, all the containers loaded with the build material have an identical flange configuration that can only be received in a magazine that dispenses the build material. All the containers loaded with the support material have a different flange configuration that can only be received in the magazine that dispenses the support material.

A protruding tip 82 is provided on the piston end 74, which expels the last material in the small opening 70. Unique to the container is a waste receptacle 60 that is provided on the plunger portion 64 for accepting delivery of waste material. Preferably there are two symmetrically opposed waste receptacles 60 for each plunger portion 64, as shown in FIG. 6. The symmetrical waste receptacles are defined by a common bottom 80 and two generally parallel sidewalls 78. The length of the side walls

are less than the distance between the side walls so that, as shown in FIG. 4, the magazine 16 can have a keyway 84 sized to only allow the containers to be inserted with the side walls 78 positioned horizontally. The side wall must be positioned horizontally in the magazine so that the indexer 44 can then rotate the containers to the appropriate position with the side walls positioned vertically prior to the container being acted on by the extrusion bar 46. Since the container is symmetrical about the common bottom 80 of the plunger portion, the containers cannot be inserted incorrectly in the magazine.

Referring back to FIG. 4, the extrusion bar acts on the plunger portion 64 to drive the plunger into the syringe portion 62 and thereby remove the build material from the container. As this occurs, the waste material 43 is deposited into the waste receptacle 60 of the plunger portion 64. Once substantially all of the material has been delivered to the dispensing device 14, the waste material is preferably sealed within the container for safe disposal. This is accomplished when the sealing end 76, shown in FIG. 5, engages the cylindrical syringe portion 62 to achieve a substantially air tight fit. Once substantially all of the material has been delivered to the dispensing device and the plunger has been sealed, the indexer barrel then rotates and ejects the sealed cartridge, as shown by numeral 66, into a waste drawer or bin 68. After the sealed cartridge 66 is ejected, the indexer then replaces the ejected container by loading a new container from the queue station.

The embodiment shown in FIG. 4 has many advantages over existing feed systems. For example, since the material is both delivered and ejected in hermetically sealed cartridges, reactive materials may be used by the SFF apparatus in an office environment without requiring special handling procedures. In addition, when the build material is a UV curable material, a UV flash cure lamp, shown by numeral 70, can be used to cure the waste material by exposing the waste material to actinic radiation after the waste material has been dispensed into the waste receptacle 60. This provides an

additional level of protection in the event an ejected cartridge is mishandled and unexpectedly damaged to the point that direct contact with the waste material becomes possible.

It is preferred that an SFF apparatus shown in FIG. 7 be provided with two feed systems, of which for the ease of illustration just one is shown in FIG. 4 at numeral 10. One feed system delivers the build material 23A, and the other delivers the support material 23B. As discussed in conjunction with the preferred containers shown in FIG. 6, the support material cartridges are configured such that they can not be inserted into the build material magazine. Likewise, the build material cartridges are configured such that they can not be inserted into the support material magazine. Such special keying of the cartridges and magazines eliminates the possibility of inadvertently mixing the materials in the apparatus. In the preferred embodiment, the waste material comprises portions of both the build material and the support material, which are delivered to the waste receptacle of the support material cartridge and build material cartridge. Preferably the waste material is delivered to the waste receptacle of a cartridge only when the cartridge is expelling material for use by the dispensing device.

In an alternative embodiment the container may comprise flexible tubes or bags instead of a cartridge to deliver the material. In addition, instead of using an extrusion bar to expel the material, a pair of rollers could be used to squeeze the material out at one end of the tube or bag. Waste material could also be delivered back into the tubes or bags on the opposite end of the tube or bag as the rollers advance forward to expel the material, similar to the manner in which a peristaltic pump operates. The tube or bag material could be transparent to actinic radiation in which case the waste material could be cured in the bag or tube by exposure to actinic radiation that passes through the thin walls of the bag or tube. The bags could then be tied or sealed prior to ejecting the waste material.

Now referring to FIG. 8, the SDM apparatus schematically shown in FIG. 7 is

shown at 10. To access the build environment, a slideable door 104 is provided at the front of the apparatus. The door 104 does not allow radiation within the machine to escape into the environment. The apparatus is configured such that it will not operate or turn on with the door 104 open. In addition, when the apparatus is in operation the door 104 will not open. A build material feed door 106 is provided so that the build material containers can be inserted into the apparatus. A support material feed door 108 is also provided so that the support material can be inserted into the apparatus. A waste drawer 68 is provided at the bottom end of the apparatus 10 so that the expelled waste containers can be removed from the apparatus. A user interface 110 is provided which is in communication with the external computer 35 previously discussed which tracks receipt of the print command data from the external computer.

What has been described are preferred embodiments in which modifications and changes may be made without departing from the spirit and scope of the accompanying claims.